



Facebook


Amazon Email: amazonsupport@gvmled.com Warehouse Add: 4301 N Delaware ave, unit D. PHILADELPHIA, PA19137, USA





PRODUCT STRUCTURE ANALYSIS





Battery power

Battery power

display button

Power input /

interface

output interface

USB power output

V buckle bayonet

Battery power indicator

Battery power display button

indicator







1

PRODUCT PARAMETER

BV-95

- Voltage: 14.8V
- Capacity: 6600mAh / 95Wh
- Maximum Discharge Current: 12A
- Maximum charging current: 6000mA
- Mount Type: V-Mount
- Charging Time: Approximately 4hours
- Operating temperature: Charging:0℃~40℃ Discharge:-20℃~60℃
- Working Temperature: -20℃~60℃
- Dimension: 150*95*45mm
- Weight: 0.7kg

BV-160

- Voltage: 14.8V
- Capacity: 10400mAh / 160Wh
- Maximum Discharge Current: 12A
- Maximum charging current: 6000mA
- Mount Type: V-Mount
- Charging Time: Approximately 6.5 hours
- Operating temperature: Charging:0℃~40℃ Discharge:-20℃~60℃

1

- Working Temperature: -20 ~60
- Dimension: 150*95*60mm
- Weight: 1kg

PRECAUTIONS

- 1 Read carefully the specification before use.
- 2 Use only recommended Li-ion charger.
- 3 Battery must be recycled properly.
- 4 Do not disppse in water or fire.
- 5 Do not disassemble or reassemble.
- 6 Do not subject to shock.
- ⑦ Do not short-circuit the battery terminals.
- 8 Do not expose to temperature above 55 /131f.

DISCLAIMERS

- **1.** Before using this product, please read the instructions carefully and make sure use the product correctly. If you don't obey the instructions and warnings, you maybe cause harm to yourself and the people around, or even damage the product and other things around.
- 2. Once you use the product, it means you have already read the disclaimer and the warnings carefully, understanding and agreeing with all the items, and promise to take responsibility of any consequences of using the product.

2